



## GFM *Folding Shredder for large areas*

Ideal for large areas, both flat and hilly, airports, cultivated and uncultivated fields and green areas – as well as areas aimed to be re-cultivated. It can be used front and rear.



## GFM *Folding Shredder for large areas*



Mod.								
			Kg	(Hp - Kw)	(g/min.)		rotore mm	
GFM - 450	4500	3000	2500	185 - 136	1000	2x16	245	2x5
GFM - 550	5500	3000	2700	185 - 136	1000	2x20	245	2x5

The technical data, specifications, characteristics and pictures are not binding for the manufacturer.

### STANDARD EQUIPMENT

- Three point linkage cat II and III cat
- Rear protection in rubber
- Front safety with zinc-plated chains
- Support foot and rubber
- Gearbox without free-wheel
- Cardan shaft for internal transmission without free-wheel
- Cap to protection of cardan
- Rotor with toothed hammers
- Belt drive
- Rear roller adjustable with scraper
- Internal counter frame
- Internal counterblades series
- Rear opening cover
- Piston at double effect for level opening
- Reinforced support hammer
- Special paint powder or liquid (Primer and enamel)

### ACCESSORIES ON REQUEST

- 1 Double Lateral skids
- 2 Reinforced roller Ø 250 mm



LIPA s.r.l.  
65010 Spoltore (PE) - Italy  
Via Castellani (ang. Via Mare Adriatico)  
Tel. +39 085 4971431 Fax +39 085 4973170  
info@lipa-srl.it [www.lipa-srl.it](http://www.lipa-srl.it)

CE  
MADE IN ITALY