

# TLBE-S

Head Shredder for excavator



Mod.			 Kg	 (g/min.)	 L/H'	 Press. BAR		 rotore mm		
TLBE-S 100	1150	1040	310	2000	50/60	220-250	10	7	140	3
TLBE-S 110	1250	1140	330	2000	60/70	220-250	11	8	140	3
TLBE-S 120	1350	1240	350	2000	60/70	220-250	12	8	140	3

The technical data, specifications, characteristics and pictures are not binding for the manufacturer.

#### STANDARD EQUIPMENT

- Linkage device
- **Hydraulic motor group 3**
- Valve anti-cavitation
- Belt drive
- Rotor with toothed hammers (on request smooth hammers)
- Internal counterframe
- Counterblades double series
- Front safety with chains
- Rear safety in rubber
- Lateral skids
- Rear adjustable roller with scraper
- Special paint powder or liquid (Primer and enamel)

#### ACCESSORIES ON REQUEST

- 1 Oscillating saddle as a replacement of standard linkage
- 2 Reinforced support hammer
- 3 Safety pin saddle\*
- 4 Pressure relief valve with flow regulator



\*Personalized saddle will be subjected to additional charge



LIPA s.r.l.  
65010 Spoltore (PE) - Italy  
Via Castellani (ang. Via Mare Adriatico)  
Tel. +39 085 4971431 Fax +39 085 4973170  
info@lipa-srl.it [www.lipa-srl.it](http://www.lipa-srl.it)

CE  
MADE IN ITALY



## TLBE-S Head Shredder for excavator

The TLBE-S shredding head is perfect for crushing grass, canes and shrubs generally up to 7 cm, located near ditches, banks, and all sorts of very steep lands. It can be applied to excavator weighing from 5 tonnes.

